

# WOODGRAIN PORCELAIN PAVERS



Archatrak



Archatrak 'Woodgrain' porcelain pavers offer the ideal paving solution where a wood look is preferred but where the decking material must be fireproof, low maintenance, wear resistant and retain its attractive appearance, year after year.

Archatrak 'Woodgrain' porcelain pavers are a high-tech alternative to both natural wood and composite wood decking. Modern porcelain tile technology coupled with advanced digital printing techniques has made possible the production of hardwearing, fade resistant, fire resistant pavers that replicate the timeless elegance and character of natural wood, with subtle variation from paver to paver, just like pieces of natural wood.

Archatrak 'Woodgrain' porcelain pavers offer all the benefits and beauty of natural wood but without the downside:

- ♦ fire proof
- ♦ stain resistant
- ♦ impervious to moisture
- ♦ no fading or color change
- ♦ highly slip resistant
- ♦ scratch and abrasion resistant
- ♦ no sealing or oiling needed
- ♦ no twisting, warping or decay
- ♦ no maintenance

All Archatrak porcelain pavers are specifically engineered for use in structural applications including elevated decks where the pavers are supported by adjustable height pedestals placed under each corner. They can also be laid directly on sand or gravel beds or placed over hard surfaces such as concrete.


## WOODGRAIN STYLES AND SIZES




All pavers are  $\frac{3}{4}$ " thick solid porcelain with rectified edges to ensure precise dimensions.

### 'Kronos Teknowood' -


designed to simulate the appearance of individual planks of wood decking. Features a distinctive ribbed surface texture with darker demarcation lines to simulate gaps between 'boards'.



**3463 Ebano**  
24" x 24"




**3468 Faggio**  
24" x 24"




**3464 Rovere**  
24" x 24"


'Kronos WoodSide' - emulates the appearance and features of reclaimed wood boards joined side by side and formed into panels or planks




**6545 Maple**  
24" x 24"




**6547 Kauri**  
24" x 24"




**6546 Oak**  
24" x 24"




**6548 Nut**  
24" x 24"



**6650 Maple**  
16" x 48"



**6652 Kauri**  
16" x 48"



**6651 Oak**  
16" x 48"



**6653 Nut**  
16" x 48"

## TECHNICAL DATA

Property	Standard	Value
Water absorption	ISO 20543/3	0.05%
Breaking strength	ISO 10545/4	3060lb
Slip resistance	ASTM C 1028/7	>0.60 wet >0.60 dry
Resistance to abrasion	ISO 10545/6	139 mm <sup>2</sup>
Impact resistance	ISO 10545/5	0.88
Static load	EN 12825	Center - 2160lbf Center point of side - 1460lbf Diagonal - 1840lbf